


Converter Box Series Hardware Specification	
Model	SDI 2 VGA (SDI2VGA-S)
Product Photo	
Description	Converts from SDI to VGA. Provides two additional SDI outputs with repeater function.
Feature	<ul style="list-style-type: none"> ● Auto source format detection (3G/HD/SD) ● Built-in hardware scaling engine with anti-aliasing ● Simultaneous 1 x VGA and 2 x SDI output ● Splitter function ● Re-clock function (for SDI output) ● 1 Mini-USB port used for: <ul style="list-style-type: none"> ➤ Brightness, contrast, hue, saturation, configuration ➤ Firmware upgrade
Input	SDI x 1
Output	D-Sub x 1 SDI x 2
SDI Format	3G-SDI (SMPTE 424M/425M) HD-SDI (SMPTE 292M) SD-SDI (SMPTE 259M)
Supported Video Format	640x480@60Hz 800x600@60Hz 1024x768@60Hz 1280x720@60Hz 1280x1024@60Hz 1400x1050@60Hz 1440x900@60Hz 1600x1200@60Hz 1920x1080@60Hz
Supported Audio Format	Up to 8 channels, 24bit, 48KHz (only available with SDI Loop-through output)
Plug & Play	✓
DC In	6V ~ 15V