


Converter Box Series Hardware Specification	
Model	Multi 2 SDI
Product Photo	
Description	Convert from DVI-D/VGA or Component/S-Video/Composite to 3G/HD/SD-SDI output
Feature	<ul style="list-style-type: none"> ● Built-in up/down conversion engine ● Video enhancement with anti-aliasing and 3D deinterlacer ● Simultaneous 2x SDI output ● Hot-keys for video mode and device configurations ● Mini-USB port for configurations and software upgrade
Input Interface	DVI-I x 1 (Support DVI-D and VGA) BNC x 3 for Component / S-Video / Composite 3.5mm Phone jack for analog audio
Output Interface	SDI x 2
Supported Video Input Format	<ul style="list-style-type: none"> ● Composite / SVideo <ul style="list-style-type: none"> ➢ NTSC / PAL ● Component <ul style="list-style-type: none"> ➢ 480i, 576i, 480p, 576p ➢ 720p, 1080i, 1080p ● DVI / VGA <ul style="list-style-type: none"> ➢ 800x600@60Hz, 1024x768@60Hz, 1280x1024@60Hz ➢ 1366x768@60Hz, 1400x1050@60Hz, 1600x1200@60Hz
Supported Video Output Format	<ul style="list-style-type: none"> ● SDI <ul style="list-style-type: none"> ➢ 1080p60/50, 1080i60/50, 1080p30/25/24, 720p60/50 ➢ 1080p59.94, 1080i59.94, 720p59.94, 1080p29.97, 1080p23.98 ➢ 525i, 625i
Audio Input Format	Stereo, 16bit, 48KHz
Audio Output Format	Stereo, 16bit, 48KHz
Plug & Play	✓
DC In	6V ~ 15V